

BLOCK PAVING SEALER

SOLVENT BASED WET LOOK ACRYLIC SEALER

DESCRIPTION

A high quality Acrylic solvent based clear sealer, designed to protect block paved areas by repelling water, dirt and oils.

USES

- > Ready for use to enhance concrete or block paving.
- > Can be brush, roller or spray applied.

COLOUR RANGE

- > Clear.

PACK SIZE

- > 5 litre and 20 litre containers.

SURFACE FINISH

- > Semi-gloss

SPREADING RATE

- > 3 – 6 square metres per litre depending on substrate and application method.

DRYING TIME

- > Surface dry in 1-2 hours. Re-coatable overnight.

SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.

PREPARATION

New blocks

Apply as soon as possible after installation. Remove excess sand. Apply above 4°C. Do not apply to wet surfaces or if rain is imminent or if efflorescence is present.

Old blocks

Fully clean off surfaces with power wash, apply detergent to suit. Allow to dry thoroughly and re-apply jointing sand before application.

APPLICATION

Britannia Block Paving Sealer can be applied by brush, roller or spray. Apply 2 coats with sufficient drying time in between. Avoid excess pooling and over coating.

CLEANING

- > For cleaning equipment use Britannia Special Solvent (Not White Spirit)

PRECAUTIONS

- > **Flammable.** Keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothing.
- > In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not breathe vapour or spray.
- > Do not empty into drains.

SAFETY

Good working practice should be followed and safety.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.

