

ACRYLIC CONCRETE SEALER

FOR CONCRETE FLOORS, CONCRETE AND FIBRE CEMENT ROOF TILES

DESCRIPTION

A high quality Acrylic solvent-based Concrete Sealer for floors and roof tiles, designed as a long lasting decorative and protective finish for application all year round.



USES

Suitable for use on concrete floors and exterior roof tiles. Excellent adhesion to porous surfaces prior to top coating.

> Can be brush or spray applied.

Not to be used on painted surfaces or high density/low suction substrates such as glazed brick, faience tiles, engineering bricks and natural slate tiles.

COLOUR RANGE

> Clear, available in several colours.

PACK SIZE

> 20 litre metal containers.

SURFACE FINISH

> Semi-gloss.

SPREADING RATE

The coverage depends on the texture and porosity of the tile surface after power washing and repair. Apply 2 coats at an overall coverage rate 2.5 - 3 square metres per litre.

DRYING TIME

Surface dry in 1-2 hours depending on temperature and porosity. Re-coatable overnight.

SHELF LIFE

> Up to 2 years if stored correctly in an unopened container.

PREPARATION AND APPLICATION

- > Clean the surface by power washing.
- > Replace broken or missing tiles and re-cement ridge/top tiles.
- > Apply Britannia Biocidal Wash solution to prevent further fungal / algal growth.
- > It can be applied throughout the year even at low temperatures to dry substrates.
- > Do not apply in wet or frosty weather or when there is a risk of the same during drying time.
- > Apply Britannia Acrylic Concrete Sealer by brush or spray.

Application Temperature should be between 5°C-25°C.

CLEANING

Equipment should be cleaned using Britannia Special Solvents. (not white spirits).



PRECAUTIONS

Do not allow flooding of material, if material is sprayed too thickly, solvent bubbling will occur, forming blisters. If these occur in the dry film, apply special solvent with rag and rub until blister disappears. Allow surface to dry normally.

- > **Flammable** keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothing.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.



Materials and Suppliers Group

SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 10 / July 2010