

FLOOR PAINT

SOLVENT BASED FLOOR PAINT FOR CONCRETE AND STONE

DESCRIPTION

A high performance mid-sheen, hard wearing polyurethane floor paint, designed to provide a cleaner, dust free, working environment. Resistant to many industrial chemicals and regular washing with water.

USES

For use on concrete and stone floors in the factory, warehouse, garage, corridor and utility room environments.

Not recommended for use on Bitumen or Asphalt.

> Can be Brush or Roller applied.

COLOUR RANGE

> Red, Grey. Other colours to order.

PACK SIZE

> 5 and 20 litre containers.

SPREADING RATE

> Up to 60 square metres per 5 litre, dependent on substrate.

DRYING TIME

> Touch dry in 2-4 hours, dependent on ambient temperature, minimum over coating time of 16-24 hours.

NOTE: Low temperatures can significantly extend the drying time.



SHELF LIFE

> Up to 2 years if stored correctly in an unopened container.

PREPARATION

All surfaces to be painted should be clean and dry, free from dust, dirt, grease, oil, laitance and loose or flaking materials.

New concrete should be allowed to mature for a minimum of 6 months before paint can be applied.

Chemically or mechanically hardened floors may need abrasion, prior to application.

If in doubt always test a small area prior to use.



APPLICATION

- > **Stir well before use.**
- > Supplied ready for use, Brush or Roller may apply Britannia Floor Paint. Coverage will vary dependent on the nature and porosity of the substrate and the application method.
- > Priming is not normally required, however the first coat on concrete or porous surfaces, should first be thinned up to 10% with white spirit and allowed to dry.
- > Britannia Floor Paint is touch dry in 2-4 hours dependent on ambient temperature.
- > Applying an even coat, 2 coats are normally required, allowing a minimum over coating time of 16-24 hours.

NOTE: Low temperatures can significantly extend the drying time.

CLEANING

- > Clean all equipment with white spirit immediately after use.

PRECAUTIONS

- > **Flammable** keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothes.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

SAFETY

- > Good working practice should be followed.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Cert: 8516



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 11 / Dec 2010