

HIGH BOND ADHESIVE ROOF PRIMER

HIGH ADHESIVE BONDING AGENT BETWEEN ASPHALT AND CONVENTIONAL BUILDING SUBSTRATES

DESCRIPTION

A high quality water-based modified rubber emulsion, designed to give a high adhesion bonding between asphalt and conventional building substrates.

USES

Britannia High Bond Primer eliminates the need for traditional methods of surface preparation i.e. roughening, scabbling, rendering and mechanical fixing. Because of its high adhesive bonding of asphalt products to building substrates such as concrete, cement render, brick and various metal. It is also suitable for use with hot and cold applied bituminous compounds.

- > Can be brush, roller or spray applied.

COLOUR RANGE

- > Orange

PACK SIZE

- > 5 litre and 20 litre containers

SPREADING RATE

- > High Bond Adhesive Roof Primer can be applied by brush, roller or spray.
- > Up to 5 square metres per litre on concrete/brick work and up to 10 square metres per litre on smooth surfaces.
- > Vertical surfaces will tend to take a slightly heavier application.



PREPARATION

The surface must be dry and free of loose and friable materials and all fungal and algal growth removed.

DRYING TIME AND APPLICATION

- > The Primer must be allowed to dry thoroughly before proceeding with asphalt or bituminous application.
- > Application temperature should be between 5°C and 25°C.
- > Do not apply in wet or frosty weather.
- > Britannia High Bond Adhesive Roof Primer is pigmented orange to assist in obtaining an even application.

SHELF LIFE

- > Up to 12 months if stored correctly in an unopened container.

CLEANING

- > Clean all equipment immediately with water after use.

PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.
- > Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environments.

SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.