

OFF-ROAD MARKING PAINT

INCREASES VISUAL CONTRAST

Safe water-based product, eco-friendly



DESCRIPTION

A high quality Acrylic water based coating for a tough, long lasting slip resistant finish on tarmac or concrete surfaces.



USES

Used to colour cycle ways, pedestrian refuges and renew and protect driveways.

> Can be brush, roller or spray applied.

Not suitable for heavy traffic areas.

Old polished granite macadams and power floated concrete areas as well as chemically or mechanically hardened floors may not be suitable for coating.

COLOUR RANGE

> Red, Green, Blue, Yellow and others to special order.

PACK SIZE

> Available in 5 litre and 20 litre drums.

SPREADING RATE

- > 6-8 square metres per litre for spray application.
- > 2-3 square metres per litre for brush or roller application.
- > Dependent on substrate, texture and porosity of the surface.
- > Apply 2 coats.

DRYING TIME

Drying is approximately 2-4 hours dependent on ambient temperature. Avoid painting when rain is expected or under poor drying conditions – below 5°C.

Curing of the coating can be extended at lower temperatures, dependent on coating thickness, substrate and texture.

SHELF LIFE

- > Up to 12 months if stored correctly in an unopened container.
- > Store above 5°C.

PREPARATION

- > All surfaces should be dry (not damp).
- > Free from loose or flaking material, dirt grease and vegetative growth.
- > Vacuum or pressure blasting with air or water may remove any debris.
- > Brushing (manual or machine) may be suitable.
- > Not to be applied if there is salt contamination or frost.



APPLICATION

- > Stir can well before use.
- > Apply an even coat either by brush, roller or by airless spray.
- > Tip size of 28 Thou is recommended for airless spray.
- > A new macadam surface should be left to oxidise for at least four weeks (longer in winter than in summer) before painting.
- > Not suitable for use on open graded macadam or other materials incorporating "cut back" bitumen.
- > New concrete should be allowed to mature for several months before coating.
- > Apply during April to October.

CLEANING

- > Clean all equipment with water immediately after use.

PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.

SITE SAFETY

DO NOT LEAVE SITE WITHOUT CHECKING THAT THE COATING HAS FULLY CURED.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Cert: 8516



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 12 / Dec 2010