

WALLSHIELD

CLEAR MASONRY WATERPROOFING SOLUTION FOR POROUS EXTERIOR WALLS

DESCRIPTION

A clear solvent based waterproofer especially formulated with damp-proof course resin to protect a variety of surfaces from the ingress of water.

USES

Designed to waterproof porous exterior walls (brickwork, stonework, cement rendering etc). Allows the surface to 'breathe' whilst still providing water repellence. Imparts **No** visual change to the surface.

- > Can be brush, roller or spray applied.

COLOUR RANGE

- > Clear, transparent solution.

PACK SIZE

- > 20 litre containers.

SPREADING RATE

- > As a guide between 40-80 square metres/20 litres (2-4 square metres/litre) dependent on porosity.
- > On surfaces with high suction the coverage may be 2 square metres per litre. Do not thin.



DRYING TIME

- > Two coats are normally applied.
- > Re-coatable as soon as the first coat has been absorbed.

SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.

PREPARATION

- > All surfaces must be dry and free from mould growth, dirt and grease.
- > Algal or Fungal deposits should first be removed by power washing the surface and then coated with Britannia's Fungicidal Wash Solution.



APPLICATION

- > Supplied ready for use by brush, roller or spray.
- > Apply a generous coat.
- > Two coats may be needed ie rough stonework. In such cases allow at least eight hours between coats.

CLEANING

- > Clean all equipment immediately with water after use.

PRECAUTIONS

- > **Flammable** keep away from sources of ignition.
- > Ensure good ventilation during application and drying.
- > Wear gloves, goggles and suitable protective clothes.
- > Keep out of reach of children.
- > In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > In case of insufficient ventilation wear suitable respiratory equipment.
- > Do not breathe vapour or spray.
- > Do not use near fishponds.
- > Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Cert: 8516



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 11 / Dec 2010