

AQUASHIELD

WATERPROOFS ROOFS INSTANTLY

EMERGENCY LEAK REPAIR

PERFORMANCE ADVANTAGES

- > Seals and waterproofs roofs on a temporary basis however bad the weather
- > Can be applied in falling rain or even under water
- > Ready to use
- > Suitable for all building surfaces
- > Solvent based

USES

Supplied ready for use on ALL BUILDING SURFACES which need immediate repair to STOP LEAKS.

- > Can be brush, roller or squeegee applied.

A full check should be required at a later date as these repairs are considered temporary.

COLOUR RANGE

- > Grey.

PACK SIZE

- > 1 and 2.5 kg containers.

SPREADING RATE

- > 1-3 kg per square metre depending on substrate and conditions.

DRYING TIME

- > Up to 6-7 days depending on temperature and thickness of coating.

SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container.



PREPARATION AND APPLICATION

Dirt build up, moss and loose material should be removed by scraping or brushing. In cold conditions any ice present on the surface must be removed.

Britannia Emergency leak repair should be applied directly to the substrate, no priming is normally required. Application by a good quality brush, roller or squeegee. Best results are achieved when "Stippled" into cracks and rough surfaces. Apply liberally to bridge small holes up to 1/8" (3mm) and larger using Britannia's Reinforcing Scrim.



IMPORTANT

- > Aquashield is not recommended for the treatment of wooden surfaces, tanking, fishponds or internal use.
- > Air conditioning vents should be sealed for a minimum of 24 hours during and after the application.

CLEANING

For all cleaning use White Spirit.

PRECAUTIONS

- > **Flammable** keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Wear gloves, goggles and suitable protective clothing.
- > In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Toxic to aquatic organisms. May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

There is a Code of practice from LRWA-“Specification and use of Liquid Applied Waterproofing Systems” on www.lrwa.org.uk which can be consulted for general advice.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Cert: 8516



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 11 / June 2023