

DRIVEWAY PAINT

SLIP RESISTANT FINISH WHICH RENEWS AND PROTECTS TARMAC

SAFE, WATER-BASED PRODUCT, EQUALLY SUITABLE FOR TARMAC OR CONCRETE SURFACES WITH A TOUGH AND LONG LASTING SLIP RESISTANT FINISH

PERFORMANCE ADVANTAGES

- > Safe water-based product, eco friendly
- > Tough and long lasting
- > Slip resistant finish
- > Equally suitable for tarmac or concrete surfaces

USES

- > Used to colour cycle ways and pedestrian refuges, renews and protects driveways, provides clear demarcation areas for indoor floors, corridors and offices.
- > Can be brush or roller applied.
- > Not suitable for heavy traffic areas.
- > Old polished granite macadams and power floated concrete areas as well as chemically or mechanically hardened floors may not be suitable for coating.

COLOUR RANGE

Black	Dark Grey	Mid Grey
Light Grey	White	Yellow
Terracotta	Tan	Forest Green

PACK SIZE

- > 5 Litres.



SPREADING RATE

- > Up to 6-8 m²/litre for brush or roller application.
- > Dependent on substrate, texture and porosity of the surface.
- > Apply 2 coats.

DRYING TIME

- > Touch Dry in 2-4 hours dependent on ambient temperature.
- > Do not drive/park on the surface for at least 24 hours.
- > Avoid painting when rain is expected or under poor drying conditions – below 5°C.
- > Curing of the coating can be extended at lower temperatures, dependent on coating thickness, substrate and texture.

SHELF LIFE

- > Up to 12 months if stored correctly in an unopened container.
- > Store within the temperature range 5°C – 25°C
- > PROTECT FROM FROST



PREPARATION

- > All surfaces should be dry (not damp).
- > Free from loose or flaking material, dirt grease and vegetative growth.
- > Vacuum or pressure blasting with air or water may remove any debris.
- > Brushing (manual or machine) may be suitable.
- > If in doubt always test a small area prior to use.
- > Not to be applied if there is salt contamination or frost.

APPLICATION

- > **STIR WELL BEFORE USE AS STAINERS USED CAN SEPARATE WITH TIME, BEST TO MIX THOROUGHLY WHEN USING DIFFERENT BATCHES.**
- > Surfaces that are cold – below 5°C – are not suitable for coating.
- > Hot surfaces – above 30°C – should be cooled with water spray before application otherwise paint will dry before film formation is completed.
- > Apply an even coat either by brush or roller.
- > A new macadam surface should be left to oxidise for at least four weeks (longer in winter than in summer) before painting.
- > Not suitable for use on open graded macadam or other materials incorporating “cut back” bitumen.
- > New concrete should be allowed to mature for several months before coating.
- > Priming is not normally required, however the first coat on concrete or porous surfaces, should first be thinned up to 10% with water and allow to dry.
- > Apply during April to October (exterior)

CLEANING

- > Clean all equipment with water immediately after use.

PRECAUTIONS

- > Keep out of reach of children.
- > In case of contact with eyes wash immediately with plenty of water.
- > Remove splashes from skin with soap and water or a recognised hand cleaner.
- > Protect from freezing.
- > Do not apply paint if there is a risk of heavy rain or frost.
- > Do not use near fishponds.

HEALTH AND SAFETY

DO NOT LEAVE SITE WITHOUT CHECKING THAT THE COATING HAS FULLY CURED.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Certificate Number 8516
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF
T: 01606 834015 F: 01606 837006 E: sales@britanniapaints.co.uk www.britanniapaints.co.uk

Version 2 / Apr 2023