

# RAINSHIELD

**WATERPROOFS ROOFS INSTANTLY**

## EMERGENCY LEAK REPAIR with fibres

### PERFORMANCE ADVANTAGES

- > Seals and waterproofs roofs on a temporary basis however bad the weather
- > Can be applied in failing rain or even under water
- > Suitable for all building surfaces
- > Ready to use
- > Solvent Based



### USES

Supplied Ready for use on ALL BUILDING SURFACES which need immediate repair to STOP LEAKS.

- > Can be poured on, brush, roller or Squeegee applied.
- > Preferred method of application is by pouring RAINSHIELD Emergency Leak Repair directly onto the area.

Not for use on wooden surfaces, tanking, fishponds or internal use.

**RAINSHIELD COATING IS NOT A PERMANENT FIX- A full check should be made at a later date as these repairs are considered temporary**

### COLOUR RANGE

- > Clear

### PACK SIZE

- > 2.5 Litre and 5 Litre containers



PLASTIC GUTTER REPAIR

### SPREADING RATE

- > Between 1 Litre - 2.5 Litres per m<sup>2</sup> dependent on substrate and conditions.

### WATER REPELLENCY

- > Rainfall immediately after application should have no adverse effect

### DRYING TIME

- > Instant waterproof protection. Touch dry in 3-4 hours and completely cured within 6-7 days.
- > The product may remain slightly soft for a further period depending on thickness and location and may whiten when applied to wet surfaces.

### SHELF LIFE

- > Up to 2 years if stored correctly in an unopened container

## PREPARATION AND APPLICATION

- > Clear all area of moss, lichen and debris by brushing to remove surface water and any other contaminants such as Oil or Grease to allow RAINSHIELD Emergency Leak repair to adhere to the surface, stop the leaks as much as possible. In cold conditions any ice present on the surface must be removed.
- > Apply a generous coat of RAINSHIELD Emergency Leak Repair Coating by Brush, Roller or squeegee at the spreading rates stated.
- > **Preferred method of application is by pouring RAINSHIELD Emergency Leak Repair directly onto the area.**
- > Best results are achieved when “stippled” into cracks and rough surfaces, apply liberally to bridge small holes up to 1/8 inch (3mm) and larger use a reinforcement scrim, embed in the first coat so that greater protection is offered, then put another coat on top to aid in stopping the leaks further.
- > Recoat again when able to waterproof further in the short term.

## IMPORTANT

- > Britannia RAINSHIELD will instantly waterproof a wide range of exposed and leaking surfaces.
- > It is ideal for EMERGENCY Leak Repair.
- > RAINSHIELD will act as a temporary repair until a full system or more permanent solution can be implemented.
- > Not recommended for treatment of wooden surfaces, tanking, fishponds or internal use.
- > Air Conditioning vents should be sealed for a minimum of 24 hours during and after the application.

## COLOUR RANGE

- > For cleaning equipment use White Spirit after use

## IMPORTANT

- > Flammable keep away from sources of ignition.
- > Ensure good ventilation during application.
- > Over occupied premises during insulation of coatings we would advise keeping windows closed.
- > Wear gloves, goggles and suitable protective clothing. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- > Remove splashes from the skin with a recognised hand cleaner or plenty of soap and water.
- > Keep out of reach of children.
- > Do not use near fishponds.
- > Toxic to aquatic organisms.
- > May cause long term adverse effects in the aquatic environments.
- > Do not empty into drains.

## SAFETY

Good working practice should be followed and safety/walking boards should be utilised where required.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

*As Britannia Paints Limited has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.*

**There is a Code of practice from LRWA-“Specification and use of Liquid Applied Waterproofing Systems” on [www.lrwa.org.uk](http://www.lrwa.org.uk) which can be consulted for general advice.**

If in doubt regarding any of the above points, please contact our technical services department for advice.

**A Material Safety Data Sheet is available on request.**

It is the users responsibility to ensure that this data sheet is current prior to using the product.



Certificate Number 8516  
ISO 9001



Unit 7/8 King Street Trading Estate, Middlewich, Cheshire CW10 9LF  
T: 01606 834015 F: 01606 837006 E: [sales@britanniapaints.co.uk](mailto:sales@britanniapaints.co.uk) [www.britanniapaints.co.uk](http://www.britanniapaints.co.uk)